## Amendments to and Listing of the Claims:

Please amend claims 1 and 12, cancel claims 4, 5, 8, and 13, and add new claims 17-21, so that the claims read as follows:

1. (Currently Amended) A three-dimensional object comprising a plurality of cured resin layers accumulated to each other, each of the cured resin layers having a shaped pattern formed by irradiating a molding surface of an actinic radiation-curable resin composition with an actinic radiation,

wherein the three-dimensional object comprises at least <u>one</u> cured resin layer comprising a sea-island microstructure in which island components are dispersed in a sea component comprising a cured polymer, the island components comprise a polymer differing from the cured resin constituting the sea component, [[and]] the island components are fine island components having a particle diameter of 20 to 2,000 nm, and the polymer constituting the island components is a polyalkylene ether compound having a number average molecular weight of 500 to 10,000.

- 2. (Original) The three-dimensional object as claimed in claim 1, wherein all of the plurality of cured resin layers constituting the three-dimensional object have the sea-island microstructure in which island components are dispersed in a sea component comprising a cured polymer, the island components comprise a polymer differing from the cured resin constituting the sea component, and the island components are fine island components having a particle diameter of 20 to 2,000 nm.
- 3. (Previously Presented) The three-dimensional object as claimed in claim 1, wherein each of the cured resin layers constituting the three-dimensional object has a thickness of 10 to 500  $\mu m$ .
  - 4. (Canceled)
  - 5. (Canceled)

- 6. (Previously Presented) The three-dimensional object as claimed in claim 1, wherein each of the cured resin layers having the sea-island microstructure has a sum of the island components of 1 to 30 % by mass with respect to the mass of the each of the cured resin layers.
- 7. (Previously Presented) The three-dimensional object as claimed in claim 1, wherein the polymer constituting the island components has a glass transition temperature of lower than 40°C.

## 8. (Canceled)

- 9. (Previously Presented) The three-dimensional object as claimed in claim 1, wherein the sea component comprises the cured resin formed by using at least one actinic radiation-polymerizable compound selected from the group consisting of a cationic-polymerizable organic compound capable of undergoing cationic polymerization upon irradiation with an actinic radiation and a radical-polymerizable organic compound capable of undergoing radical polymerization upon irradiation with an actinic radiation.
- 10. (Previously Presented) The three-dimensional object as claimed in claim 1, wherein the sea component comprises the cured resin formed by using both of a cation-polymerizable organic compound and a radical-polymerizable organic compound.
- 11. (Previously Presented) The three-dimensional object as claimed in claim 9, wherein the cation-polymerizable organic compound is a compound having an epoxy group, and the radical-polymerizable organic compound is a compound having a (meth)acryl group.
- 12. (Currently Amended) A method of producing a three-dimensional object having a sea-island microstructure as claimed in claim 1, which comprises:

irradiating a molding surface of an actinic radiation-curable resin composition with an actinic radiation to form a cured resin layer having a shape pattern; and

repeating a fabricating procedure comprising: providing an actinic radiation-curable resin composition for one layer on a cured resin layer to form a molding surface; and irradiating the molding surface with an actinic radiation to form a cured resin layer having a shape pattern, so as to produce the three-dimensional object comprising a plurality of cured resin layers accumulated,

wherein the fabricating procedure is performed by using an actinic radiation-curable resin composition comprising a homogeneous mixture of actinic radiation-curable resin component with a component to become polymeric island components having a particle diameter of 20 to 2,000 nm upon irradiation, and the actinic radiation-curable resin component is capable of forming a cured resin as a sea component upon the irradation

a) at least one actinic radiation-polymerizable compound as the cured resin of the sea component, selected from the group consisting of a cationic-polymerizable organic compound capable of undergoing cationic polymerization upon irradiation with an actinic radiation and a radical-polymerizable organic compound capable of undergoing radical polymerization upon irradiation with an actinic radiation.

## with

b) a polyalkylene ether compound having a number-average molecular weight of 500 to 10,000 as the polymer to become polymeric island components, wherein the polymeric island components have a particle diameter of 20 to 2,000 nm upon irradiation.

## 13. (Canceled)

- 14. (Previously Presented) The method as claimed in claim 12, wherein the cationic polymerizable organic compound is a compound having an epoxy group, and the radical polymerizable organic compound is a compound having a (meth)acryl group.
- 15. (Previously Presented) The method as claimed in claim 12, wherein a content of the polymer to become the polymeric island components is from 1 to 30 % by mass with respect to the mass of the actinic radiation-curable resin composition used for forming the cured resin layer having the sea-island microstructure.
- 16. (Previously Presented) The method as claimed in claim 12, wherein the actinic radiation-curable resin composition comprises an oxetane compound together with a cationic-polymerizable organic compound having an epoxy group.
- 17. (New) A three-dimensional object comprising a plurality of cured resin layers accumulated to each other, each of the cured resin layers having a shaped pattern formed by irradiating a molding surface of an actinic radiation-curable resin composition with an actinic radiation,

wherein the three-dimensional object comprises at least one cured resin layer comprising a sea-island microstructure in which island components are dispersed in a sea component comprising a cured polymer, the island components comprise a polymer differing from the cured resin constituting the sea component, the island components are fine island components having a particle diameter of 20 to 2,000 nm,

and wherein the island components in each of the cured resin layers having the sea-island microstructure do not exist in an upper portion of the each of the cured resin layers, the upper portion being located in an actinic radiation-irradiated surface of the each of the cured resin layers, and the island components exist in a portion from a bottom part of the each of the cured resin layers to an upward part along the thickness of the each of the cured resin layers.

7

- 18. (New) The three-dimensional object as claimed in claim 17, wherein the upper portion containing no island component has a thickness of 2 to 10% with respect to the thickness of the each of the cured resin layers.
- 19. (New) The three-dimensional object as claimed in claim 17, wherein each of the cured resin layers having the sea-island microstructure has a sum of the island components of 1 to 30 % by mass with respect to the mass of the each of the cured resin layers.
- 20. (New) The three-dimensional object as claimed in claim 17, wherein the polymer constituting the island components is a polyalkylene ether compound having a number average molecular weight of 500 to 10,000.
- 21. (New) The three-dimensional object as claimed in claim 17, wherein the sea component comprises the cured resin formed by using both of a cation-polymerizable organic compound and a radical-polymerizable organic compound.